

# TEMPIL<sup>o</sup>, INC.

2901 Hamilton Blvd.  
South Plainfield, NJ 07080  
PHONE: 908-757-8300

# MATERIAL SAFETY DATA SHEET

MSDS NO: TS- 110<sup>o</sup>C  
DATE: June 10, 2000  
EMERGENCY NO: 800-424-9300 FAX: 908-757-9273

## SECTION 1 MATERIAL IDENTIFICATION

PRODUCT NAME: **TEMPILSTIK 110<sup>o</sup>C/ 230<sup>o</sup>F**  
GENERIC NAME OR FAMILY: Temperature Indicating Product  
SHIPPING NAMES: **DOT: Non-regulated**

IATA: Non-regulated

HAZARDOUS COMPONENTS OF MIXTURE	WEIGHT %	OSHA PEL (PPM)	ACGIH TLV (PPM)	CAS Number
Acetanilide	85-90	N.E.	N.E.	103-84-4
Non-hazardous ingredients	10-15			

## SECTION 313 SUPPLIER NOTIFICATION

This product contains the following toxic chemical (s) subject to the reporting requirements of section 313 of the Emergency Planning and Community Right-to-Know Act of 1986 and of CFR 372:

Chemical Name	%	CAS Number
Not applicable		

## SECTION 2 PHYSICAL DATA

BOILING POINT (°F): N.E.	SPECIFIC GRAVITY (H <sub>2</sub> O = 1): N.E.
VAPOR PRESSURE (mm Hg.): N.E.	PERCENT VOLATILE BY VOLUME (%): N.A.
VAPOR DENSITY (AIR =1): N.E.	EVAPORATION RATE (N-Butyl Acetate = 1) : N.A.
SOLUBILITY IN WATER: Slight	VOLATILE ORGANIC COMPOUNDS (VOC) : N.A.
APPEARANCE AND ODOR: Crayon like solid stick	

## SECTION 3 FIRE AND EXPLOSION HAZARD DATA

FLASH POINT ( and Method): N.E.	FLAMMABLE LIMITS	<u>LOWER</u> N.E.	<u>UPPER</u> N.E.
---------------------------------	------------------	----------------------	----------------------

EXTINGUISHING MEDIA: Water fog, CO<sub>2</sub> , dry chemical, foam

SPECIAL FIRE FIGHTING PROCEDURES: Wear self contained breathing apparatus and protective clothing.

UNUSUAL FIRE AND EXPLOSION HAZARDS: Material will melt and char in the presence of open flames.

## SECTION 4 - REACTIVITY HAZARD DATA

<input type="checkbox"/> STABILITY: Stable	CONDITIONS TO AVOID: Not applicable
Incompatibility (Materials to Avoid): Alkalis	

Hazardous Decomposition Products: Thermal decomposition will release NO<sub>x</sub> vapors

HAZARDOUS POLYMERIZATION: Will not occur

CONDITIONS TO AVOID: Not Applicable

## SECTION 5 - CONTROL AND PROTECTIVE MEASURES

Respiratory Protection (Specify Type): NIOSH approved respirator if ventilation is insufficient.

Protective Gloves: Rubber

Eye Protection: Safety glasses

### VENTILATION TO BE USED

Local Exhaust

Mechanical(general): If local exhaust is insufficient

Other Protective Clothing & Equipment: Not normally required.

Hygienic Work Practices: Wash hands thoroughly after using this product.

## SECTION 6 - HEALTH HAZARD DATA

### PRIMARY ROUTES OF ENTRY

Inhalation

Skin Absorption

### HEALTH HAZARDS

Acute: Inhalation may cause respiratory irritation. Contact with skin may cause dermatitis.

Signs & Symptoms of Exposure: Possible irritation.

Target Organ Information: Unknown

**EMERGENCY FIRST AID PROCEDURES** - Seek medical assistance for further treatment, observation and support if necessary.

Eye Contact: Flush eyes with water for 15 minutes.

Skin Contact: Wash thoroughly with soap and water.

Inhalation: Remove to fresh air. If breathing is difficult, obtain medical attention.

Ingestion: Obtain immediate medical attention.

## SECTION 7 - PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken if Material Is Spilled or Released: Sweep up and hold in bag for waste disposal.

Waste Disposal Methods: Dispose of in accordance with all Federal, State and local laws.

Precaution to be taken in Handling & Storage: Store in cool, dry area. Avoid skin contact. Avoid breathing vapors.

Other Precautions and/or Special Hazards: Not applicable

HMIS rating: 0= Minimal hazard

1= Slight hazard

2= Moderate hazard

3= Serious hazard

4= Severe hazard

**Health: 3 Flammability: 1 Reactivity: 1**

This information contained herein is furnished without warranty of any kind. Employers should use this information only as a supplement to other information gathered by them and must make independent determinations of suitability and completeness of information from all sources to assure proper use of these materials and the safety and health of employees.