

Boodo

High-performance Model | Fully Protective Sheet Laser Cutting Machine













Optional


Laser Scanning Cutting The Speed Pioneer in Thin Sheet Processing

The pioneer of laser scanning cutting technology breaks through the limits of thin sheet perforation, boosting cutting efficiency by up to 150%, and becoming the most powerful thin sheet processing tool to date.





Conventional Laser Cutting





Laser Scanning Cutting Principle











Intelligent Recognition

seams without manual measurement.



image information. Adaptive adjustment of the process

parameters. Achieve precise compensation for cutting





Automatic Compensation




Automatic Nozzle Changer

35s of rapid automatic nozzle changing, intelligent calibration of cutting distance. Halve time costs, and avoid the risks associated with manual operation. Automatic cleaning of the nozzle ensures simple and worry-free daily maintenance.













5-year Warranty for Bodor Self-developed Three Core Laser Components


With our perfect integration technology for the self-developed BodorThinker control system, BodorPower laser source, and BodorGenius laser head, we can extend the service warranty for these three core components to five years! The three core components are designed, produced, tested, and delivered in an integrated manner, working perfectly together to make the equipment run more stably and efficiently. At the same time, it greatly reduces the risk of component contamination and failure rate, extends the lifespan, and lowers maintenance costs by avoiding repeated assembly.



Control System

Laser Source

Laser Head









High-performance Model

Sheet Laser Cutting Machine

Applicable Industries

Widely applied in engineering, agricultural manufacturing, special purpose motor vehicle manufacturing, mining machinery and coal machinery manufacturing, sheet metal processing and other industries.













P Series Parameters

	P3	P4	P6	P12
Working Area	3048mm×1524mm	4000mm×2000mm	6500mm×2500mm	12500mm×2600mm
Max. Linkage Speed	200m/min	200m/min	200m/min	200m/min
Max Accelaration	4.0 G	4.0 G	2.8 G	2.8 G
One-Click Processing	•	•	•	•
Remnant Layout	(Intelligent Remnants Layout)	•	•	•
One-Second Edge Finding	(not available when bevel cutting is selected)	•	•	•
Active Obstacle Avoidance	•	•	•	•
Automatic Cutting Seam Compensation	•	×	×	×
Automatic Nozzle Changer	8 Nozzles (not available when beveling cutting is selected)	8 Nozzles (not available when beveling cutting is selected)	8 Nozzles (not available when beveling cutting is selected)	8 Nozzles (not available when beveling cutting is selected)
Air Pressure Intelligent Control	●12kW and above	●12kW and above	●12kW and above	●12kW and above
Automatic Adjustment of Cutting Gas Pressure	•	•	•	



