



**Welding process**

- MIG/MAG short spray manual arc welding

**Materials**

- Carbon steels
- Aluminized and galvanized steels
- Stainless steels
- Aluminum and aluminum alloys

**Applications**

- Light job shop fabrication
- Medium-heavy job shop fabrication
- Building sites
- Automobile industry
- Repair and overhaul
- Handicraft working
- Vehicle bodywork repair
- Building
- Installers
- Stand construction workers
- Door and window fitters
- Blacksmiths
- Workshops



**Technical features**

- Extremely rugged, reliable and easy-to-use systems
- Heavy duty and environmental conditions, high service life
- High temperature, shockproof, abrasion resistant plastic case
- Excellent performances also with long power supply extension cables
- Built-in wire feeder unit (2/4 rolls drive)
- Fully Selco designed wire drive unit
- Wire feed push-button
- Ø 200/300 mm wire spool compatible
- Multiple output choke selection
- 2/4 step operating mode
- Perfect arc ignition (motor slope)
- Burn-back and droplet detachment correction
- Spot welding mode
- Euro adaptor - MIG/MAG torch compatible

**Power source**

Icon	Input	Output	P	X%	Icons	I <sub>2</sub>	U <sub>0</sub>	IP	mm l x w x h	Kg
Neomig 3000	3x230V	20A	13,8kVA 13,2kW	40°C 30% 300A 40°C 60% 230A 40°C 100% 180A 25°C 35% 300A 25°C 60% 250A 25°C 100% 200A	2x10	30-320A	42V	21S	980x500x760mm	88,0kg
	3x400V	16A	13,8kVA 13,2kW	40°C 30% 300A 40°C 60% 230A 40°C 100% 180A 25°C 35% 300A 25°C 60% 250A 25°C 100% 200A		30-320A	42V	21S	980x500x760mm	88,0kg
Neomig 4000	3x230V	35A	22,2kVA 21,3kW	40°C 30% 400A 40°C 60% 320A 40°C 100% 250A 25°C 35% 400A 25°C 60% 340A 25°C 100% 270A	3x10	30-420A	53V	21S	980x500x760mm	107,0kg
	3x400V	20A	22,2kVA 21,3kW	40°C 30% 400A 40°C 60% 320A 40°C 100% 250A 25°C 35% 400A 25°C 60% 340A 25°C 100% 270A		30-420A	53V	21S	980x500x760mm	107,0kg

**Wirefeeder**

Icon	P	φ (m/min)	φ (mm)	Icons	Ø mm	φ	Icons	Icon
Neomig 3000 SL 4R-1T (v.2R)	90W	1,5-18m/min	200/300mm	2 ● 4 ○	1,0/1,2mm ● 0,6-1,6mm ○ A 0,8-1,6mm ○ Z 1,2-2,4mm ○	●	●	
Neomig 4000 SL 4R-1T (v.2R)	90W	1,5-18m/min	200/300mm	2 ● 4 ○	1,0/1,2mm ● 0,6-1,6mm ○ A 0,8-1,6mm ○ Z 1,2-2,4mm ○	●	●	

● = Included ○ = Optional

A = Aluminum Z = Cored

Part No.	Description
<b>Neomig 3000 - MIG/MAG welding configuration</b>	
51.06.03001	NEOMIG 3000 230/400V
71.05.020	WORK CABLE - 35mm <sup>2</sup> - L.4m
81.01.031	MIG/MAG WELDING TORCH MB 26 KD - L.4m - AIR COOLED
72.01.007	PRESSURE LIMITER - IT
<b>Neomig 4000 - MIG/MAG welding configuration</b>	
51.06.04001	NEOMIG 4000 230/400V
71.05.025	WORK CABLE - 50mm <sup>2</sup> - L.4m
81.01.041	MIG/MAG WELDING TORCH MB 36 KD - L.4m - AIR COOLED
72.01.007	PRESSURE LIMITER - IT
<b>Accessories</b>	
<b>Torch</b>	
81.01.031	MIG/MAG WELDING TORCH MB 26 KD - L.4m - AIR COOLED
81.01.041	MIG/MAG WELDING TORCH MB 36 KD - L.4m - AIR COOLED
<b>Earth cable</b>	
71.05.020	WORK CABLE - 35mm <sup>2</sup> - L.4m
71.05.025	WORK CABLE - 50mm <sup>2</sup> - L.4m
<b>Other</b>	
72.01.007	PRESSURE LIMITER - IT
72.01.003	PRESSURE LIMITER WITH FLOWMETER
72.04.001	ARGON-CO2 GAS FITTING
07.01.507	UPGRADE KIT FROM 2 ROLLS (1 ROLL DRIVE) TO 4 ROLLS (2 ROLLS DRIVE)